


<b>Projet:</b>	<b>Type:</b>	<b>Qté:</b>
----------------	--------------	-------------

**Ceiling Light 12" 24W 120V 2700-3500-4000-5000-6000K**

Easy to install and integrated with a CCT selection option, the Speclite ceiling light will simplify your project. Equipped with a dip switch to select your preferred lighting color between 3000K, 4000K, and 5000K, this light fixture is compatible with 120V (AC) and is available in 2 different finishes (White and Black) and 2 different sizes (9" and 12"). The Speclite ceiling light is perfect for creating a customized lighting ambiance while being easy to install and use. Its sleek design and flexibility make it an ideal choice for modernizing residential and commercial interiors.



**CHARACTERISTICS**

- Integrated 3CCT Selection: Choose from three color temperatures for lighting that suits any atmosphere.
- Wide Compatibility: Operates on 120VAC and allows for quick installation and maintenance with Wago connectors.
- TRIAC Dimming: Compatible with Triac dimmers for precise light intensity control.
- Diffuse and Comfortable Lighting: Provides soft, even light, ideal for creating a calming atmosphere.



**NOMENCLATURE**

SERIE	DIMENSIONS	LENS	BODY COLOUR	VOLTAGE	CCT	MAX POWER	OPTIONS 1	OPTIONS 2	VER.
CE	12	F	W	A	C	024	0	D	V2
Ceiling light	12"	frost	white	120V	2700-3500-4000-5000-6000K	24W	N/A	dim TRIAC	V2

**PHOTOMETRIC SPECIFICATIONS**

LUMENS	3,000
CCT	2700-3500-4000-5000-6000K
ANGLE	140°
C.R.I.	80
DIMMABLE	Triac
PHOTOCELL	N/A
SENSOR	N/A
LUMEN MAINTENANCE L70	50,000 hrs
LED TYPE	SMD2835
LED QTY	192
LED VOLTAGE	72V
LED MAX CURRENT	300mA
FLICKER	Flicker-Free

**MECHANICAL SPECIFICATIONS**

HOUSING MATERIAL	Polycarbonate
HOUSING FINISH	White
LENS MATERIAL	Polycarbonate
LENS FINISH	Frost
WEIGHT	0.90 KG
OPERATING TEMP.	-10°C ~ 40°C

**ELECTRICAL SPECIFICATIONS**


REAL POWER	24 W
VOLTAGE	120V
EFFICIENCY	125 lm/w
POWER FACTOR	97 %
T.H.D	20 %
FREQUENCY	50/60Hz

**CERTIFICATIONS**

REGULATORY LISTING	cETL
EFFICIENCY LISTING	Energy Star
DLC ID	
FCC	Yes
BARCODE	882110008103
ENVIRONMENTAL	IP44
IK PROTECTION	
SURGE PROTECTION WITH GROUNDING	1.5KV
SURGE PROTECTION WITHOUT GROUNDING	0.9KV

<b>APPLICATION</b>	Indoor
<b>INSTALLATION</b>	Surface Mount
<b>CABLE LENGTH</b>	N/A

## DIMENSIONS




## PACKAGING

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
30.70 cm X 30.70 cm X 3.00 cm	32.50 cm X 32.50 cm X 32.50 cm	10	9.10 kg	270 
12 1/8 " X 12 1/8 " X 1 1/8 "	12 3/4 " X 12 3/4 " X 12 3/4 "		20.06 lbs	

## PRODUCTS IMAGES



Compatible with Junction Boxes



Compatible Dimmers

Brand	Model	Image	Match	Brand	Model	Image	Match
LUTRON	MACL-153MR-WH		5★	Leviton	6672-1LW		5★
LUTRON	SCL-153P-WH		5★	Leviton	DSL06-1LZ		3★
LUTRON	PD-6WCL-WH		5★	Leviton	6674-P0W		3★
LUTRON	CTCL-153P-WH		5★	Leviton	IPL06-10Z		3★
LUTRON	MSCL-OP153M-WH		4★	 <p>100% - 5% Smooth trac dimming, compatible with most LED dimmers in North America market.</p>			
LUTRON	DVCL-153P-WH		3★				
LUTRON	DWW-603PGH-WH		2★				