

<b>Projet:</b>	<b>Type:</b>	<b>Qté:</b>
----------------	--------------	-------------

**T8 4ft 2pin 20-18-15-12W 120-347V 2700K-4000K-5000K-6500K**

The SpecLite 4-foot T8 tube is designed with an aluminum extrusion to maximize heat dissipation and a polycarbonate lens to extend its lifespan. This T8 tube effectively replaces your traditional T8 and T12 fluorescent tubes with G13 pins. Switching to LED reduces energy consumption by up to 55%, providing an eco-friendly and cost-effective solution. This model offers five selectable CCT color temperatures and adjustable wattage on a single tube, and is compatible with 120-347V power, meeting all your lighting needs. What sets the SpecLite tube apart is its unique installation flexibility: it can be installed with or without a ballast, connected at both ends or just one, making it a truly universal installation solution. Perfect for upgrading your commercial or industrial lighting systems, this LED tube not only reduces operating and maintenance costs but also improves energy efficiency and lighting quality.



**CARACTERISTICS**

- Maximizes heat dissipation with an extruded aluminum heat sink.
- CCT color choice between 2700K and 6500K on the same tube.
- Power choice between 10W (1400LM) and 22W (2860LM) on the same tube.
- Universal installation: with or without ballast and compatible with 120-347VAC power input.



**NOMENCLATURE**

SERIE	LENGHT	WIRING	BASE TYPE	VOLTAGE	CCT	MAX POWER	LENS	CONNECTION TYPE	VER.
T8	4	2	G13	F	C	020	F	B	Z
T8	4ft	both ends wiring	2pin	120-347V	2700K-4000K-5000K-6500K	20-18-15-12W	frost	ballast bypass	Z

**PHOTOMETRIC SPECIFICATIONS**

<b>LUMENS</b>	2,900
<b>CCT</b>	2700-4000-5000-6500K
<b>ANGLE</b>	120
<b>C.R.I.</b>	83
<b>DIMMABLE</b>	N/A
<b>PHOTOCELL</b>	N/A
<b>SENSOR</b>	N/A
<b>LUMEN MAINTENANCE L70</b>	75,000 hrs
<b>LED TYPE</b>	
<b>LED QTY</b>	
<b>LED VOLTAGE</b>	
<b>LED MAX CURRENT</b>	
<b>FLICKER</b>	Not Flicker-Free

**MECHANICAL SPECIFICATIONS**

<b>HOUSING MATERIAL</b>	Aluminium
<b>HOUSING FINISH</b>	Grey
<b>LENS MATERIAL</b>	Polycarbonate
<b>LENS FINISH</b>	Frost
<b>WEIGHT</b>	0.35 KG
<b>OPERATING TEMP.</b>	-40°C ~ 40°C

**ELECTRICAL SPECIFICATIONS**


<b>REAL POWER</b>	20 W
<b>VOLTAGE</b>	120-347V
<b>EFFICIENCY</b>	145 lm/w
<b>POWER FACTOR</b>	97.8 %
<b>T.H.D</b>	7.4 %
<b>FREQUENCY</b>	50/60Hz

**CERTIFICATIONS**

<b>REGULATORY LISTING</b>	cETL
<b>EFFICIENCY LISTING</b>	DLC Standard
<b>DLC ID</b>	S-ZNMTCJ
<b>FCC</b>	No
<b>BARCODE</b>	882110007229
<b>ENVIRONMENTAL</b>	N/A
<b>IK PROTECTION</b>	N/A
<b>SURGE PROTECTION WITH GROUNDING</b>	2
<b>SURGE PROTECTION WITHOUT GROUNDING</b>	1.2

<b>APPLICATION</b>	Indoor
<b>INSTALLATION</b>	Retro-Fit
<b>CABLE LENGTH</b>	N/A

**DIMENSIONS**



**PACKAGING**

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
121.00 cm X 3.00 cm X 3.00 cm 47 5/8 " X 1 1/8 " X 1 1/8 "	N/A	N/A	0.00 kg 0.00 lbs	32 

**PRODUCTS IMAGES**

No Product images

SPECLITE.CA | INFO@SPECLITE.CA | TEL: 1-855-533-8818  
**HEADQUARTER:** 600-1111 BOUL. DR.-FREDERICK-PHILIPS MONTRÉAL, QC H4M 2X6  
**WAREHOUSE:** 1710 AUTOROUTE TRANSCANADIENNE, DORVAL, QC, H9P 2X7