

Wall Cylinder

10W/20W/30W | 3CCT | 120-347V

Suitable for indoor and outdoor applications including retail stores, event spaces, hospitality venues, condominiums, building entrances, and more!



120-347V
Universal Driver
0-10V dimming

Power Selectable
10W / 20W / 30W

Powder
Coat Finish
black

Colour Selectable
3000K / 4000K / 5000K

Direct / Indirect
50% uplight, 50% downlight

Built-in Photocell
unplug to bypass

Packaged in Eco-friendly
Packaging
without plastic

Cylinder Rings Illuminate



TECHNICAL DATA



LIGHT SPECIFICATIONS

Efficacy	112 lm/W
CCT	3000K/4000K/5000K
CRI	>80
Distribution	Direct / Indirect (50% downlight, 50% uplight)
Beam Angle	60°
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year
Factory Settings	30W 4000K

LUMEN OUTPUT			
	3000K	4000K	5000K
10W	913 lm	913 lm	972 lm
20W	2086 lm	2192 lm	2230 lm
30W	2796 lm	3079 lm	3203 lm

APPROVALS & LISTINGS

cUL	E482965
-----	---------

DIMENSIONS AND WEIGHTS

Fixture Weight	3.13 lbs
Fixture Dimensions	4.72 x 10.35 x 4.76 in
Master Carton Qty	6
Master Carton Weight	22.84 lbs
Master Carton Dimensions	16.14 x 11.81 x 11.42 in
Carton Qty	1
Carton Weight	3.44 lbs
Carton Dimensions	11.22 x 5.12 x 5.31 in

ELECTRICAL

Wattage	10W/20W/30W
Voltage	120-347V
Current	0.2A
Surge Protection	6kV
Auxiliary Output	N/A
Power Factor	0.9
THD	≤15%
Operating Temp	-40 to 50°C

CONSTRUCTION

Housing	Die-Cast Aluminum
Lens	Glass
Finish	Powder Coated
Finish Colour	Black
IP Rating	IP65

DIMENSIONAL DRAWINGS (IN)

