

**Projet:** \_\_\_\_\_ **Type:** \_\_\_\_\_

**Wall Pack Mini 26W 100-277V 5000K**

**CHARACTERISTICS**

- 120° lens for effective lighting
- Equipped with a photocell to automate control
- Robust construction to withstand the most difficult conditions
- DLC Premium and eligible to the maximum subsidy



**NOMENCLATURE**

SERIE	BEAM ANGLE	LENS	BODY COLOUR	VOLTAGE	CCT	MAX POWER	OPTIONS 1	OPTIONS 2	VER.
WL	00	C	R	D	5	026	0	P	ML
Wall pack mini	120°	clear	bronze	100-277V	5000K	26W	N/A	int. photo.	ML

**PHOTOMETRIC SPECIFICATIONS**

LUMENS	3,542
CCT	5000K
ANGLE	120°
C.R.I.	71
DIMMABLE	N/A
PHOTOCELL	Integrated Photocell
SENSOR	N/A
LUMEN MAINTENANCE L70	75,000 hrs
LED TYPE	SMD2835
LED QTY	30
LED VOLTAGE	60V DC
LED MAX CURRENT	390mA
FLICKER	Not Flicker-Free

**MECHANICAL SPECIFICATIONS**

HOUSING MATERIAL	Die casting Aluminium
HOUSING FINISH	Bronze
LENS MATERIAL	Polycarbonate
LENS FINISH	Clear
WEIGHT	0.80 KG
OPERATING TEMP.	-40°C ~ 50°C
APPLICATION	Outdoor

**ELECTRICAL SPECIFICATIONS**

REAL POWER	25.6 W
VOLTAGE	100-277V
EFFICIENCY	138.36 lm/w
POWER FACTOR	88.9 %
T.H.D	17.6 %
FREQUENCY	50/60Hz

**CERTIFICATIONS**

REGULATORY LISTING	cETL
EFFICIENCY LISTING	DLC Premium
DLC ID	PJUSW7BW
FCC	
BARCODE	882110004662
ENVIRONMENTAL	IP65
IK PROTECTION	IK08
SURGE PROTECTION WITH GROUNDING	4KV
SURGE PROTECTION WITHOUT GROUNDING	2.4KV

<b>INSTALLATION</b>	Wall Mount
<b>CABLE LENGTH</b>	N/A

## DIMENSIONS



## PACKAGING

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
25.00 cm X 17.00 cm X 11.00 cm 9 7/8 " X 6 3/4 " X 4 3/8 "	N/A	N/A	1.00 kg 2.20 lbs	24 

## PRODUCTS IMAGES

