

Project:	
Ordering info:	
Submitted by:	Date:



Linear Pendant Luminaire ZNTH60-PD (Direct) ZNTH60-PDI (Direct/Indirect)	PD	Wattage Range	Lumen Range	Efficacy	Light Performance												
	24-79W	3,262-11,000lm	138lm/W	816-1,375lm/ft													
	PDI	Wattage Range	Lumen Range	Efficacy	Light Performance												
		↓25-79W ↑21-70W	↓3,380-10,869lm ↑2,839-9,631lm	136lm/W	↓826-1,359lm/ft ↑710-1,204lm/ft												
	3CCT Selectable 3000K 3500K 4000K		Finishes Black White														
3 CCT 120-347V 0-10V + CRI + 80 ETL Intertek Damp Humid 5 years warranty guarantee DLC LISTED PREMIUM	<table><thead><tr><th></th><th>L</th><th>W</th><th>H</th></tr></thead><tbody><tr><td>4FT</td><td>1200mm 47.24"</td><td>60mm 2.36"</td><td>85mm 3.35"</td></tr><tr><td>8FT</td><td>2390mm 94.09"</td><td>60mm 2.36"</td><td>85mm 3.35"</td></tr></tbody></table>						L	W	H	4FT	1200mm 47.24"	60mm 2.36"	85mm 3.35"	8FT	2390mm 94.09"	60mm 2.36"	85mm 3.35"
	L	W	H														
4FT	1200mm 47.24"	60mm 2.36"	85mm 3.35"														
8FT	2390mm 94.09"	60mm 2.36"	85mm 3.35"														

Ordering Guide Example: ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/B/B6/S6/B

Family/ Series	Mounting		Function	Length		Diffuser Direct		Diffuser Indirect		Max Total Lumens		CCT 30/35/40K	CRI	Voltage		Driver		Housing Finish		
ZNTH60	P	Pendant	D	Direct	4	4ft	F	Frosted	-	-	05L	5000 (4ft)	MK3	80	UN3	120-347V	D1	0-10V Dim 1%	W	White
					8	8ft					10L	10000 (8ft)							B	Black
			DI	Direct/ Indirect	4	4ft	F	Frosted	F	Frosted	10L	10000 (4ft)							C	Custom
					8	8ft					20L	20000 (8ft)								

Cord Colour/Length	Suspension Length	Canopy Colour
W6 White 6ft B6 Black 6ft	S6 6ft	W White B Black C Custom

Light Outputs

Catalogue Code	Voltage	Dimension			CCT	Efficacy lm/W	CRI	Direct			UP Light		
		L	W	H				Watts	Delivered Lumens	Lumens per foot	Watts	Delivered Lumens	Lumens per foot
ZNTH60-PD/4	120-347V	47.24"	2.36"	3.35"	30K-35K-40K	130	80+	39	5300	1325	-	-	-
								32	4349	1087	-	-	-
								24	3262	816	-	-	-
								79	11000	1375	-	-	-
ZNTH60-PD/8	120-347V	94.09"	2.36"	3.35"	30K-35K-40K	130	80+	63	8772	1097	-	-	-
								48	6684	836	-	-	-
								39	5273	1318	32	4327	1082
								32	4327	1082	26	3515	879
ZNTH60-PDI/4	120-347V	47.24"	2.36"	3.35"	30K-35K-40K	130	80+	25	3380	845	21	2839	710
								79	10869	1359	70	9631	1204
								63	8668	1084	58	7980	998
								48	6604	826	46	6329	791

Project:	
Ordering info:	
Submitted by:	Date:



Specifications

Housing:	The Zenith60 housing is constructed of extruded aluminum 6063T5.	Power Feed:	The unit comes complete with 18/5 STW 600V rated power cable (White or Black) preinstalled with internal quick connect. For row mounting the power feed is easily removed where not needed.
End Caps:	Die cast aluminum fastened to housing with internal fasteners.	Suspension:	Galvanized 1.5mm (1/16") aircraft cable with fully adjustable grippers for ease of on-site leveling. All suspension points are field adjustable along the length of a unit. 【Joiner Kit is included with fixture, to be used for Row Mounting.】
Optics:	Frosted polycarbonate snap in lens with Lambertian distribution.	LED:	Name brand LED with long life offered in standard 80+ CRI. On board selectable CCT offers maximum flexibility (3000K/3500K/4000K).
Driver:	LED drivers are contractor wattage selectable and universal 120-347V input (up to 3 different outputs – see output chart). Less than 20%THD and 0-10V dimmable down to 1%. The drivers of the Direct/Indirect units can be adjusted independently of each other allowing maximum flexibility.	Finish:	Polyester powder painted finish

Model & Ordering Information

Ordering Code	DLC Premium	Model Number	Description	Case QTY
3695002	Yes	ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/B/B6/S6/B	4Ft., Direct, Selectable 40-33-25W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	4
3695001	Yes	ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/W/W6/S6/W	4Ft., Direct, Selectable 40-33-25W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	4
3696002	Yes	ZNTH60-PD/8/F/10L/MK3/80/UN3/D1/B/B6/S6/B	8Ft., Direct, Selectable 80-66-50W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	2
3696001	Yes	ZNTH60-PD/8/F/10L/MK3/80/UN3/D1/W/W6/S6/W	8Ft., Direct, Selectable 80-66-50W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	2
3695004	Yes	ZNTH60-PDI/4/F/F/10L/MK3/80/UN3/D1/B/B6/S6/B	4Ft., Direct/Indirect, Selectable 40-33-25W Down, 33-28-22W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	4
3695003	Yes	ZNTH60-PDI/4/F/F/10L/MK3/80/UN3/D1/W/W6/S6/W	4Ft., Direct/Indirect, Selectable 40-33-25W Down, 33-28-22W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	4
3696004	Yes	ZNTH60-PDI/8/F/F/20L/MK3/80/UN3/D1/B/B6/S6/B	8Ft., Direct/Indirect, Selectable 80-66-50W Down, 66-56-44W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	2
3696003	Yes	ZNTH60-PDI/8/F/F/20L/MK3/80/UN3/D1/W/W6/S6/W	8Ft., Direct/Indirect, Selectable 80-66-50W Down, 66-56-44W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	2
3690001	-	ZNTH60-K1	10Ft., Suspension, Power Cable White & 2 Aircraft Cable Kit.	-
3690002	-	ZNTH60-K2	10Ft., Suspension, Power Cable Black & 2 Aircraft Cable Kit.	-
3690004	-	ZNTH60-K4	Joiner Kit, for Row mounting.	-

Mounting

