



GET YOUR PRODUCTS FAST
Arani is committed to same day shipping on orders before 3pm*.

Date:

Project:

Prepared for:

Type:

Comments:

4FT LED T8 TUBE VERSION 9

DIRECT CONNECT INPUT



SPECIFICATIONS

Direct Connect Input
120-277V

Suitable for Enclosed Fixtures

Housing Material: Glass + PET protector Film

Beam Angle: 240°

Colour Rendering Index: >80

Functioning Temperature: -20°C to 40°C

No UV or IR Radiation

Non-dimmable

AVAILABILITY

4FT

4000K / 5000K



*This icon indicates a STOCK item:
Look for this Same Day Shipping icon below in 'Ordering Information' for products that ship on the same day (orders placed before 3pm) from Montreal, Quebec / Calgary, Alberta



Full IES File Available on Request




LED T8 Tube V9
T48T8-15W-xxK-V9


INSTALLATION

1. Turn off the power to the light fixture at the breaker panel before installation.
2. Open the diffuser from the light fixture.
3. Remove the flurescent tubes and the ballast. Please dispose of these items properly as they contain mercury.
4. Put Led tubes into the lighting fixture.
5. Install the LED tubes, close the diffuser.

Make the electrical connections on both sides.



Make the electrical connections on one side. Pay attention to the label on the tube which marks clearly which end is short-circuit.



ORDERING INFORMATION

SERIES	LENGTH	PINS	POWER (WATTS)	EQUIVALENT TO (WATTS)	LUMENS	INPUT VOLTAGE	COLOR TEMP	PRODUCT ID	MODEL NUMBER	ORDERING CODE
LED T8 TUBES V9	4FT	2	15	32	1900	120-277V	4000K	S-Q4OIGK	TUB48L0015W-40KF015-V9	T48T8-15W-40K-V9
							5000K	S-WO94MI	TUB48L0015W-50KF015-V9	T48T8-15W-50K-V9