

Date:	Project:
Prepared for:	Type:
Comments:	

COMMERCIAL OUTLETS






OU1C-15A-TR-WH-V2
(Front View)



OU1C-20A-TR-WH-V2
(Front View)



OU1C-15A-TR-WH-V2
(Rear View)



SPECIFICATIONS

Characteristics

- Back & Side Wire
- Selfgrounding
- Commercial Grade
- Tamper Resistant
- Weather Resistant



Input voltage	125Vac
Rated Working Current	15A / 20A
Maximum power	1875W (15A) / 2500W (20A)
Environment	Suitable for Dry Locations.
Wire size	#12- #14 AWG
Conductor Material	Solid copper only
Color Options	White
Weight	60g
Material	Polycarbonate Body with Copper Contacts
Warranty	5 Years
Certifications	cULus
Dielectric voltage	Withstands 2000V per UL498
Flammability	Rated V-2 per UL94
Operating Temperature	-40°C to 60°C

ORDERING INFORMATION:

Stock item. Same Day Shipping for orders placed by 3pm EST

SERIES	FINISH	RATED WORKING CURRENT	ORDERING CODE
COMMERCIAL OUTLETS	WHITE	15A	OU1C-15A-TR-WH-V2
		20A	OU1C-20A-TR-WH-V2

