

Date:	Project:
Prepared for:	Type:
Comments:	

## RESIDENTIAL OUTLETS






OU1-15A-TR-BK-V2  
(Front view)



OU1-20A-TR-WH-V2  
(Front view)



OU1-15A-TR-WH-V2  
(Rear view)



### SPECIFICATIONS

#### Characteristics

- Back & Side Wire
- Selfgrounding
- Residential Grade
- Tamper Resistant



<b>Input voltage</b>	125Vac
<b>Rated Working Current</b>	15A / 20A
<b>Maximum power</b>	1875W (15A) / 2500W (20A)
<b>Environment</b>	Suitable for Dry Locations.
<b>Wire size</b>	#12- #14 AWG
<b>Conductor Material</b>	Solid copper only
<b>Color Options</b>	White / Black
<b>Weight</b>	60g
<b>Material</b>	Polycarbonate Body with Copper Contacts
<b>Warranty</b>	2 Years
<b>Certifications</b>	cULus
<b>Dielectric voltage</b>	Withstands 2000V per UL498
<b>Flammability</b>	Rated V-2 per UL94
<b>Operating Temperature</b>	-40°C to 60°C

### ORDERING INFORMATION:

Stock item. Same Day Shipping for orders placed by 3pm EST

SERIES	RATED WORKING CURRENT	FINISH	ORDERING CODE
RESIDENTIAL OUTLETS	15A	WHITE	OU1-15A-TR-WH-V2
		BLACK	OU1-15A-TR-BK-V2
	20A	WHITE	OU1-20A-TR-WH-V2
		BLACK	OU1-20A-TR-BK-V2

