

Projet: Type: Qté:

Area Light V2 200W 277-480V 3500K

CARACTERISTICS

- -
- -
- -
- -



NOMENCLATURE

| SERIE | BEAM ANGLE | LENS | BODY COLOUR | VOLTAGE | CCT | MAX POWER | OPTIONS 1 | OPTIONS 2 | VER. |
|------------|------------|-------|-------------|----------|-------|-----------|------------------|-------------|------|
| AL | 05 | C | R | H | 3 | 200 | P | P | ML |
| Area light | type5 | clear | bronze | 277-480V | 3500K | 200W | twist lock photo | int. photo. | ML |

PHOTOMETRIC SPECIFICATIONS

| | |
|-----------------------|---|
| LUMENS | 0 |
| CCT | |
| ANGLE | |
| C.R.I. | |
| DIMMABLE | |
| PHOTOCELL | |
| SENSOR | |
| LUMEN MAINTENANCE L70 | |
| LED TYPE | |
| LED QTY | |
| LED VOLTAGE | |
| LED MAX CURRENT | |
| FLICKER | |

MECHANICAL SPECIFICATIONS

| | |
|------------------|---------|
| HOUSING MATERIAL | |
| HOUSING FINISH | |
| LENS MATERIAL | |
| LENS FINISH | |
| WEIGHT | 0.00 KG |
| OPERATING TEMP. | |
| APPLICATION | |
| INSTALLATION | |
| CABLE LENGTH | N/A |

ELECTRICAL SPECIFICATIONS

| | |
|--------------|----------|
| REAL POWER | W |
| VOLTAGE | 277-480V |
| EFFICIENCY | lm/w |
| POWER FACTOR | % |
| T.H.D | |
| FREQUENCY | |

CERTIFICATIONS

| | |
|------------------------------------|---|
| REGULATORY LISTING | |
| EFFICIENCY LISTING | |
| DLC ID | |
| FCC | |
| BARCODE | 0 |
| ENVIRONMENTAL | |
| IK PROTECTION | |
| SURGE PROTECTION WITH GROUNDING | |
| SURGE PROTECTION WITHOUT GROUNDING | |

DIMENSIONS



PACKAGING

| DIMENSION INNER CARTON | DIMENSION OUTER CARTON | QUANTITY MASTER | MASTER WEIGHT | PALLET QUANTITY |
|------------------------|------------------------|-----------------|---------------------|---|
| N/A | N/A | N/A | 0.00 kg 0.00 lbs |  |

PRODUCTS IMAGES

No Product images

SPECLITE.CA | INFO@SPECLITE.CA | TEL: 1-855-533-8818
HEADQUARTER: 600-1111 BOUL. DR.-FREDERICK-PHILIPS MONTRÉAL, QC H4M 2X6
WAREHOUSE: 1710 AUTOROUTE TRANSCANADIENNE, DORVAL, QC, H9P 2X7