

LED FIXTURE

DL Series



LED Wrap Around DL-WA2, WA3

WA2 (2' / 4' hinged wrap light)
WA3 (4' Eco-wrap light), newly added 120-347V auto-sensing driver



5-year limited warranty

Operating temperature range -20 °C ~ +40 °C




Features & Benefits

- cULus listed, DLC*
- 0-10V dimmable*, L70 @*
- Wall or ceiling mounted
- PMMA Lens
- Shallow profile, excellent for low ceilings applications
- Damp location rated, High CRI (80+)

* For applicable models, see product specification below

Dimensional Drawing



	L	W	H
WA2/2F	24.5"	7.09"	2.8"
WA2/4F	48"	7.09"	2.8"
WA3	48.6"	6.5"	2.5"

Ordering Information Example: DL-WA2/4F/40W/40/UNV/D/EM

Family Name	Fixture Type	Size	Wattage	CCT	Voltage	Dimmable	Options**
DL (Deltalum)	WA2	2F (2')	25W	35 (3500K)	UNV (120-277V)	D (Dimmable)	S (Microwave sensor) EM(Emergency battery)
		4F (4')	40W	40 (4000K)			
	WA3	42W	50 (5000K)				
		MW (Selectable Wattage)	MK (Selectable Kelvin)				

- ** • Microwave can penetrate walls or glass thinner than 20cm, movement in adjacent corridors may be detected.
- Detection area will be affected by speed of motion, mounting height and movement volume.
- Installation shall not be mounted to avoid false trigger caused by the luminaire itself shaking. (Rooftop HVAC, upper floor vibration, etc.)
- Shall not be installed next to large operating machines such as ventilator/ceiling fan to avoid false triggering caused by machine vibration.
- They cannot penetrate metal. Large metal object near the sensor may create a "dead zone" behind it.
- Microwave sensors have advantage over PIR device in that they can operate in hot environments, however, they are sensitive devices and can be prone to false detection by everyday items like ceiling fans, moving branches or curtains, loose packaging, etc.

Other options may be available, consult Turolight Sales. Specifications and data are subject to change without notice.

Product Specification

Ordering Code	DLC	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Beam Angle	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Damp Location	M.O.L (inch)	Case QTY.
3664124	-	DL-WA2/2F/25W/40/UNV/D	25	120-277V	100,000	120°	3275	4000	>80	Yes	24.5	4
3665161	-	DL-WA2/4F/40W/35/UNV/D	40	120-277V	100,000	120°	5200	3500	>80	Yes	48	4
3665135	-	DL-WA2/4F/40W/40/UNV/D	40	120-277V	100,000	120°	5240	4000	>80	Yes	48	4
3665162	-	DL-WA2/4F/40W/35/UNV/D/S	40	120-277V	100,000	120°	5200	3500	>80	Yes	48	4
3665165	-	DL-WA2/4F/40W/40/UNV/D/S	40	120-277V	100,000	120°	5240	4000	>80	Yes	48	4
-	-	DL-WA2/4F/40W/40/UNV/D/EM	40	120-277V	100,000	120°	5240	4000	>80	Yes	48	4
3682245	-	DL-WA2/4F/MW/MK/120-347V/D	40-35-30	120-347V	100,000	120°	5200-4550-3900	35-40-50	>80	Yes	48	4
3665137	-	DL-WA3/4F/42W/40/UNV	42	120-277V	100,000	120°	4700	4000	>80	Yes	48.6	4
3665138	-	DL-WA3/4F/42W/50/UNV	42	120-277V	100,000	120°	4704	5000	>80	Yes	48.6	4
3665309	Y	DL-WA3/4F/42W/35/120-347V	42	120-347V	100,000	120°	5460	3500	>80	Yes	48.6	4
3665310	Y	DL-WA3/4F/42W/40/120-347V	42	120-347V	100,000	120°	5502	4000	>80	Yes	48.6	4
3660052	-	DL-WA2/2F/LENS	DeltaLum hinged-wrap light 2ft. Replacement PMMA lens									
3660053	-	DL-WA2/4F/LENS	DeltaLum hinged-wrap light 4ft. Replacement PMMA lens									
3660054	-	DL-WA3/4F/LENS	DeltaLum Eco-wrap light 4ft. Replacement PMMA lens									