

Projet: Type: Qté:

Linear Retrofit 65-60-50-40-30W 120-347V 3500-4000-5000-5700-6500K

The Speclite retrofit kit is a light fixture designed to convert existing fluorescent strip lights to LED. Featuring a sturdy metal housing with spring fittings, it is compatible with all 4' and 8' fluorescent strip widths. This fixture is equipped with two dip switches for selecting color temperature (CCT: 3500K, 4000K, 5000K) and adjusting power during installation. It also includes multiple circuit breakers, simplifying end-to-end installation and maintenance. Additionally, the Speclite retrofit kit comes with an occupancy sensor compatible with our universal remote, making it an ideal solution for electricians seeking quick and easy-to-install lighting that is both flexible and cost-efficient for commercial spaces.

CARACTERISTICS

- Integrated 3CCT selection (from 3500K to 5000K) and 5 power levels (from 65W to 30W): Allows complete customization of lighting to suit different needs and environments.
- Quick and easy installation with an adjustable base that allows retrofitting most traditional tube fixtures. Simplified daisy-chaining with quick-connectors for up to 15 units on 120VAC and 20 units on 347VAC.
- Integrated occupancy sensor: Easily configure settings via the remote control with LCD screen (model ZZHU-HD05R, sold separately) for smart lighting management.
- DLC Premium Certified: Maximize eligibility for energy subsidies, ensuring additional savings on your installation and operating costs.



NOMENCLATURE

SERIE	DIMENSIONS	LENS	BODY COLOUR	VOLTAGE	CCT	MAX POWER	OPTIONS 1	OPTIONS 2	VER.
LR	04	F	W	F	C	065	D	M	SS
Linear Retrofit	4ft	frost	white	120-347V	3500-4000-5000-5700-6500K	65-60-50-40-30W	dim 0-10V	motion	SS

PHOTOMETRIC SPECIFICATIONS

LUMENS	8,580
CCT	3500-4000-5000-5700-6500K
ANGLE	120
C.R.I.	83
DIMMABLE	0-10V DC
PHOTOCELL	N/A
SENSOR	Motion & Lighting sensor
LUMEN MAINTENANCE L70	100,000 hrs
LED TYPE	SMD2835
LED QTY	540
LED VOLTAGE	130VDC
LED MAX CURRENT	480mA
FLICKER	Flicker-Free

ELECTRICAL SPECIFICATIONS

REAL POWER	63.2 W
VOLTAGE	120-347V
EFFICIENCY	135.76 lm/w
POWER FACTOR	94 %
T.H.D	15 %
FREQUENCY	50/60Hz

CERTIFICATIONS


REGULATORY LISTING	cUL
EFFICIENCY LISTING	DLC Premium
DLC ID	S-6WFX1M
FCC	No
BARCODE	882110007373
ENVIRONMENTAL	IP40
IK PROTECTION	IK06
SURGE PROTECTION WITH GROUNDING	2.5KV
SURGE PROTECTION WITHOUT GROUNDING	2.5KV

MECHANICAL SPECIFICATIONS

HOUSING MATERIAL	Aluminium, Powder Coated
HOUSING FINISH	White
LENS MATERIAL	Polycarbonate
LENS FINISH	Frost
WEIGHT	1.80 KG

OPERATING TEMP.	-25°C ~ 40°C
APPLICATION	Indoor
INSTALLATION	Retro-Fit
CABLE LENGTH	5'


DIMENSIONS



PACKAGING

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
123.00 cm X 10.00 cm X 4.00 cm	128.00 cm X 30.50 cm X 25.50 cm	6	13.80 kg	72 
48 3/8 " X 3 7/8 " X 1 5/8 "	50 3/8 " X 12 " X 10 "		30.42 lbs	

PRODUCTS IMAGES



SPECLITE.CA | INFO@SPECLITE.CA | TEL: 1-855-533-8818
HEADQUARTER: 600-1111 BOUL. DR.-FREDERICK-PHILIPS MONTRÉAL, QC H4M 2X6
WAREHOUSE: 1710 AUTOROUTE TRANSCANADIENNE, DORVAL, QC, H9P 2X7