

SPECIFICATION

NEXLEDS®

NEXLEDS LTD



2 inch
3 inch
4 inch



VIDEO



Deep anti-glare
LED Downlight

NX-2XAGDL-6W-5CCT-W / NX-3XAGDL-12W-5CCT-W

NX-4XAGDL-15W-5CCT-W

Specification

PRODUCT NAME :	DEEP ANTI-GLARE LED DOWNLIGHT
MODEL NO. :	NX-2XAGDL-6W-5CCT-W / NX-3XAGDL-12W-5CCT-W NX-4XAGDL-15W-5CCT-W
SPECIFICATION :	AC120Vac, 60Hz; 0.12A, 6W / 0.12A, 12W / 0.15A, 15W
WORKING TEMP :	-20~50(°C)
POWER FACTOR :	>0.9
CRI(RA) :	>90
COLOR :	White
LIGHT SOURCE :	COB
LUMEN :	100 lm/W
LIFE TIME :	50000 hrs
BEAM ANGLE :	24°
PRODUCT SIZE :	2.44*2.99 inch / 3.3*3.82 inch / 4.17*4.88 inch
CUTOUT SIZE :	2.17 inch / 2.95 inch / 3.74 inch
IP :	Suitable for Damp location
APPLICATION :	Home, shop, hotel..etc
WARRANTY :	5 years
STANDARD :	ETL
COLOR TEMP :	2700K-3000K-3500K-4000K-5000K Changeable , Dimmable

Feature:

- 1.cETLus safety standard certified.
- 2.The connection box is made of aluminum material.
- 3.Two quick connectors for easy installation.
- 4.Anti-glare design downlight
- 5.Excellent dimming effect, real 0-100% dimmable.
- 6.High-brightness COB light source
- 7.Professional neutral color box packaging.

Dimension:



Installation:

1. Turn off the power before installation.
2. Connect the commercial power with the matched power supply.
Make sure no copper wire is exposed.
3. Connect the matched power supply and downlight through the DC plug.
4. Fix the downlight and power supply in a safe place.
5. Turn on the power.

Dimension:

1. Confirm whether the package is complete or not before installation.
2. The Led downlight should be driven by an appointed power supply.
3. Keep away from supply before cleaning the downlight.
4. Final interpretation is owned by NEXLEDS.

