

SPECIFICATION

NEXLEDS®

NEXLEDS LTD



5 CCT Changeable

3 inch
4 inch



VIDEO



LED DOWNLIGHT

NX-3A0GDL-12W-5CCT-W / NX-4A0GDL-12W-5CCT-W

Specification

PRODUCT NAME :	LED DOWNLIGHT
MODEL NO. :	NX-3A0GDL-12W-5CCT-W / NX-4A0GDL-12W-5CCT-W
SPECIFICATION :	AC120Vac, 60Hz, 0.12A, 12W
WORKING TEMP :	-20~50(°C)
POWER FACTOR :	>0.9
CRI(RA) :	>90
COLOR :	White
LIGHT SOURCE :	COB
LUMEN :	80 LM/W
LIFE TIME :	50000 hrs
BEAM ANGLE :	24°
PRODUCT SIZE :	3.25*2.52 inch / 3.66*2.83 inch
CUTOUT SIZE :	2.95 inch / 3.35 inch
IP :	Suitable for Damp location
APPLICATION :	Home, shop, hotel..etc
WARRANTY :	5 years
STANDARD :	ETL
COLOR TEMP :	2700K-3000K-3500K-4000K-5000K Changeable ,Dimmable

Feature:

- 1.cETLus safety standard certified.
- 2.The connection box is made of aluminum material.
- 3.Two quick connectors for easy installation.
- 4.Anti-glare design downlight
- 5.Excellent dimming effect, real 0-100% dimmable.
- 6.12 watts 1200 lumens with high brightness COB light source
- 7.Professional neutral color box packaging.

Dimension:



Installation:

- 1.Turn off the power before installation.
- 2.Connect the commercial power with the matched power supply.
Make sure no copper wire is exposed.
- 3.Connect the matched power supply and downlight through the DC plug.
- 4.Fix the downlight and power supply in a safe place.
- 5.Turn on the power.

Dimension:

- 1.Confirm whether the package is complete or not before installation.
- 2.The Led downlight should be driven by an appointed power supply.
- 3.Keep away from supply before cleaning the downlight.
- 4.Final interpretation is owned by NEXLEDS.

