

|                |              |             |
|----------------|--------------|-------------|
| <b>Projet:</b> | <b>Type:</b> | <b>Qté:</b> |
|----------------|--------------|-------------|

**Flat panel 3CCT Back-lit 40-30-25-20-15W 120-347V 3500-4000-5000-5700-6500K**

The SpecLite panel is designed for commercial applications requiring efficient and economical lighting. Equipped with a lightweight and corrosion-resistant aluminum housing, which is more durable than standard metallic materials, it allows for easy and quick installation thanks to its tool-free, openable design. This light fixture also features a dip switch that allows you to select the color temperature (CCT: 3000K, 4000K, 5000K, 5700K, 6500K) and the desired power during installation. Additionally, the fixture includes an integrated circuit breaker, making maintenance easier. Ideal for electricians looking to provide flexible and economical lighting solutions for commercial spaces. SpecLite LED panels are also available in standard sizes of 1x4, 2x4, and 2x2 to fit various configurations.



**CARACTERISTICS**

- Integrated selection of 5 color temperatures (CCT) and 5 power levels: Provides maximum flexibility to customize lighting based on the specific needs of each project.
- Quick and easy installation: Designed for effortless setup, significantly reducing installation time.
- 0-10V Dimming: Allows precise brightness adjustment down to 10% for optimal energy consumption management.
- DLC Premium Certified: Ensures maximum eligibility for energy subsidies, guaranteeing additional savings.

**NOMENCLATURE**

| SERIE       | DIMENSIONS | LENS  | BODY COLOUR | VOLTAGE  | CCT                       | MAX POWER       | OPTIONS 1     | OPTIONS 2 | VER. |
|-------------|------------|-------|-------------|----------|---------------------------|-----------------|---------------|-----------|------|
| PB          | 22         | F     | W           | F        | C                         | 040             | M             | D         | SS   |
| Panel light | 2x2        | frost | white       | 120-347V | 3500-4000-5000-5700-6500K | 40-30-25-20-15W | motion sensor | dim 0-10V | SS   |

**PHOTOMETRIC SPECIFICATIONS**

|                              |                          |
|------------------------------|--------------------------|
| <b>LUMENS</b>                | 5,075                    |
| <b>CCT</b>                   | 3500/4000/5000K          |
| <b>ANGLE</b>                 | 120°                     |
| <b>C.R.I.</b>                | 82                       |
| <b>DIMMABLE</b>              | 0-10V DC                 |
| <b>PHOTOCELL</b>             | N/A                      |
| <b>SENSOR</b>                | Motion & Lighting sensor |
| <b>LUMEN MAINTENANCE L70</b> | 50,000 hrs               |
| <b>LED TYPE</b>              | SMD 2835                 |
| <b>LED QTY</b>               | 96                       |
| <b>LED VOLTAGE</b>           | 100-150V                 |
| <b>LED MAX CURRENT</b>       | 0.265A                   |
| <b>FLICKER</b>               | Flicker-Free             |

**MECHANICAL SPECIFICATIONS**

|                         |               |
|-------------------------|---------------|
| <b>HOUSING MATERIAL</b> | Steel         |
| <b>HOUSING FINISH</b>   | White         |
| <b>LENS MATERIAL</b>    | Polycarbonate |
| <b>LENS FINISH</b>      | Frost         |

**ELECTRICAL SPECIFICATIONS**


|                     |             |
|---------------------|-------------|
| <b>REAL POWER</b>   | 40.1 W      |
| <b>VOLTAGE</b>      | 120-347V    |
| <b>EFFICIENCY</b>   | 126.88 lm/w |
| <b>POWER FACTOR</b> | 90.4 %      |
| <b>T.H.D</b>        | 19 %        |
| <b>FREQUENCY</b>    | 50/60Hz     |

**CERTIFICATIONS**

|   |              |
|---|--------------|
| <b>REGULATORY LISTING</b>                 | cETL         |
| <b>EFFICIENCY LISTING</b>                 | DLC Premium  |
| <b>DLC ID</b>                             | S-YT33R7     |
| <b>FCC</b>                                |              |
| <b>BARCODE</b>                            | 882110007649 |
| <b>ENVIRONMENTAL</b>                      | IP40         |
| <b>IK PROTECTION</b>                      |              |
| <b>SURGE PROTECTION WITH GROUNDING</b>    | 2KV          |
| <b>SURGE PROTECTION WITHOUT GROUNDING</b> | 2KV          |

|                        |                                       |
|------------------------|---------------------------------------|
| <b>WEIGHT</b>          | 0.00 KG                               |
| <b>OPERATING TEMP.</b> | -25°C ~ 40°C                          |
| <b>APPLICATION</b>     | Indoor                                |
| <b>INSTALLATION</b>    | Recessed, Surface Mount,<br>Suspended |
| <b>CABLE LENGTH</b>    | N/A                                   |

## DIMENSIONS



## PACKAGING

| DIMENSION INNER CARTON        | DIMENSION OUTER CARTON | QUANTITY MASTER | MASTER WEIGHT | PALLET QUANTITY   |
|-------------------------------|------------------------|-----------------|---------------|---|
| 64.50 cm X 65.50 cm X 8.00 cm | N/A                    | N/A             | 4.70 kg       | 50  |
| 25 3/8" X 25 3/4" X 3 1/8"    |                        |                 | 10.36 lbs     |   |

## PRODUCTS IMAGES





SPECLITE.CA | INFO@SPECLITE.CA | TEL: 1-855-533-8818  
**HEADQUARTER:** 600-1111 BOUL. DR.-FREDERICK-PHILIPS MONTRÉAL, QC H4M 2X6  
**WAREHOUSE:** 1710 AUTOROUTE TRANSCANADIENNE, DORVAL, QC, H9P 2X7