| Projet: | Type: | Qté: |
|---|---|---|

## Linear Fixture NA NA NA

The Speclite linear light fixture is designed for commercial applications requiring efficient and cost-effective lighting. Available in 4-foot and 8-foot lengths, it features a tool-free openable metal housing, allowing for quick and easy installation. This fixture is also equipped with a dip switch to select the color temperature (CCT: 3500K, 4000K, 5000K) and the desired wattage during installation. Additionally, the linear fixture is ready to accommodate an occupancy sensor, either infrared or microwave, for intelligent lighting control. It also includes an integrated circuit breaker, making maintenance easier. Ideal for electricians looking to provide flexible and economical lighting solutions for commercial spaces

### CARACTERISTICS

- Integrated 3CCT and 3 power selection: Easily adjust color temperature and wattage during installation for maximum versatility.
- Quick and easy installation: The metal housing opens without tools, making installation easier and reducing time and effort required.
- Ready to accommodate a Speclite occupancy sensor, which connects via a plug & play connector and installs without screws using magnetic mounting.
- DLC Premium Certified: Maximize your savings with increased eligibility for energy subsidies.

### NOMENCLATURE

| SERIE | VER. |
|---|---|
| NA | |
| NA | |

### PHOTOMETRIC SPECIFICATIONS

| | |
|---|---|
| LUMENS | 10,400 |
| CCT | |
| ANGLE | |
| C.R.I. | |
| DIMMABLE | |
| PHOTOCELL | |
| SENSOR | |
| LUMEN MAINTENANCE L70 | |
| LED TYPE | |
| LED QTY | |
| LED VOLTAGE | |
| LED MAX CURRENT | |
| FLICKER | |

### MECHANICAL SPECIFICATIONS

| | |
|---|---|
| HOUSING MATERIAL | |
| HOUSING FINISH | |
| LENS MATERIAL | |
| LENS FINISH | |
| WEIGHT | 0.00 KG |
| OPERATING TEMP. | |

### ELECTRICAL SPECIFICATIONS

| | |
|---|---|
| REAL POWER | W |
| VOLTAGE | |
| EFFICIENCY | lm/w |
| POWER FACTOR | % |
| T.H.D | |
| FREQUENCY | |

### CERTIFICATIONS

| | |
|---|---|
| REGULATORY LISTING | |
| EFFICIENCY LISTING | |
| DLC ID | S-CHQAEJ |
| FCC | |
| BARCODE | 882110007090 |
| ENVIRONMENTAL | |
| IK PROTECTION | |
| SURGE PROTECTION WITH GROUNDING | |
| SURGE PROTECTION WITHOUT GROUNDING | |

| APPLICATION | |
| --- | --- |
| INSTALLATION | |
| CABLE LENGTH | N/A |

**DIMENSIONS**



**PACKAGING**

| DIMENSION INNER CARTON | DIMENSION OUTER CARTON | QUANTITY MASTER | MASTER WEIGHT | PALLET QUANTITY |
|---|---|---|---|---|
| 247.00 cm X 11.00 cm X 10.00 cm | N/A | N/A | 4.00 kg |  |
| 97 1/4 ″ X 4 3/8 ″ X 3 7/8 ″ | | | 8.82 lbs | |

**PRODUCTS IMAGES**

No Product images