

LED FIXTURE

SEL Series



LED Round High Lumen HighBay SEL-RHB

120-347V auto-sensing driver, 0-10V dimming
Selectable Wattage & Selectable Kelvin (CCT)



5-year limited warranty

Operating temperature range -40° C ~ +55° C



Features & Benefits

cULus listed, DLC Premium and NSF rated

System light efficacy 170 LPW, 120-347V auto-sensing driver

White finish, with 3M cable


90° beam spread, PC Lens

Sensor socket supplied and capable

CRI \geq 80, L70 @ 50,000 hrs

IP65, wet location rated

Dimensional Drawing



H	D
7.28"	15.4"

Ordering Information Example: SEL-RHB/300XL/MW/MK/120-347V/HK/D

Family Name	Fixture Type	Wattage	CCT	Voltage	Installation	Dimmable
SEL (Select)	RHB (Round High Bay)	300XL/MW (Selectable Wattage, Max. 300W)	MW (Selectable CCT)	120-347V	HK (Hook)	D (0-10V dimming)

Product Specification

Ordering Code	DLC Premium	Model Number	Description	Wattage (W)	Input Voltage (V)	Hour Rating (L70)	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Wet Location	Dimension D x H (inch)	Case QTY.
3682233	Yes	SEL-RHB/300XL/MW/MK/120-347V/HK/D	SEL-RHB HighBay, Selectable-W 300W-270W-240W (51000-45900-40800lm), Selectable 40-50K, 120-347V, 0-10V Dimming c/w Sensor socket (Sensor ordered separately). 10' Power & 10'LV Cords White	300-270-240	120-347V	50,000	51000-45900-40800	40-50	>80	Yes	15.4x7.28	1
3660159	-	SSL-CHB/LV/12V/SENSOR	LED 12V DC microwave sensor (w/o socket), -25°C ~ +60°C									
3660160	-	SSL-CHB/LV/12/CONTROLLER	12V DC microwave sensor remote control (required for programming)									