

1100 PROFILE




Scale 1:1



The 1100 series is a shallow, rectangular, and flangeless profile. It is designed to be discrete and integrates into most surfaces. The 1100 series offers a wide selection of lenses, and LED platforms to choose from for a beautifully finished luminaire with end caps.

PRODUCT FEATURES

- Recess into millwork using standard woodworking tools for a 0.75 in. (19 mm) groove
- Stainless steel mounting hardware for peace of mind integration
- Custom lengths with precision to $1/16$ (0.0625) inches
- Internal groove guide for easy application of LED strip when field installation is needed
- A selection of lenses to meet task at hand
- Aluminum construction for superior heat dissipation
- UL 2108 listed - Suitable for storage and closet areas




Scale 1:1

LINEAR WEIGHT MAXIMUM LED STRIP WIDTH

0.060 lbs / ft DRY: 9 / 16 "
0.089 kg / m DRY: 14 mm


LED TAPE COMPATIBILITY



CHANNEL COLOR OPTIONS



MOUNTING



LOCATION RATING



dry

OTHER OPTIONS



dot-free

USEFUL LINKS



[MAXIMUM LED RUN CHART PER DRIVER](#)



[VOLTAGE DROP CHART](#)



[INSTALLATION SHEET](#)



[IES FILES](#)



UNDER SHELF 45° ANGLE

Mount the channel behind a valance at a 45 degree angle to keep it and the light source hidden from direct view.

Code e.g.: CA1101-**MC3**-DRS-LE200-K27-AID-FH6-WSB-QE60 PND



COVE AND ACCENT

Mounted within our pre-fabricated Gypsum Cove series (Nidus in this image) for seamless and easy cove installation (to be ordered separately). Refer to the spec sheets: [Apsis](#), [Latus](#), [Nidus*](#), [Sulcus](#).

Code e.g.: CA1100-**M3M**-DXS-LT300-K42-AID-FH9-WSB-QE72 P010



RECESSED IN MILLWORK

Use here in a toe kick the channel is designed to fit in a 0.75 in. groove for a clean flangeless look within the millwork.

Code e.g.: CA1101-**MCF**-DXS-LP4-K30-AIM-FH9-WSB-Q036 PPH




SURFACE INDIRECT


Create a glow or accent on the ceiling above or below cabinets.

Code e.g.: CA1100-**MCF**-DRS-LP300-K35-AID-FH6-WSE-Q048 P010

1 Finish	2 Mounting	3 Optics	4 Lumen Package	5 CCT	6 Application	7 Power Feed	8 Input / Output	9 Exact / Optimal	10 Length, in	11 Driver Type
-	-	-	-	-	AID	-	-	-	-	-

1 PROFILE & FINISH	2 MOUNTING	3 OPTICS	4 LUMEN PACKAGE	5 CCT	6 APPLICATION
CA1100 - Anodized aluminum finish CA1101 - Anodized black finish CA110W - White (special order) CA110X - Custom color provide RAL #	MCF - Flat surface bracket MC3 - 45° Corner bracket MC8 - Swivel 180° M3M - Double face mounting tape MNO - No mounting	DCS - Clear lens DXS - Optiflex lens DOS - Opal lens DRS - Prime lens DBS - Black lens DSS - Silens DODS - 3D Opal drop square lens DNO - No lens	LP100 - 1.5 W/ft - >130 lm/ft LP200 - 2.9 W/ft - >200 lm/ft LP300 - 4.4 W/ft - >300 lm/ft LP450 - 5.8 W/ft - >450 lm/ft LP750** - 7.0 W/ft - >550 lm/ft PRECISE LE150* - 1.5 W/ft - >150 lm/ft LE300 - 3.0 W/ft - >300 lm/ft LE600 - 5.5 W/ft - >600 lm/ft NEAT LT150* - 2.0 W/ft - >150 lm/ft LT300 - 3.0 W/ft - >300 lm/ft PEAK LK900 - 7.5 W/ft - >900 lm/ft LW2229 - WARMDIM 2200-2900K - 4.4 W/ft - 192 lm/ft LW2735 - WARMDIM 2700-3500K - 4.4 W/ft - 202 lm/ft LWC2230 - WARMDIM COB 2200-3000K - 4.4 W/ft - 323 lm/ft	K24 - 2400K K27 - 2700K K30 - 3000K K35 - 3500K K40 - 4000K **K50 - 5000K (LP750 only) <i>*LE150 and LT150 are only available in K27 and K30</i>	AID - Indoor dry locations


7 POWER FEED	8 INPUT / OUTPUT	9 EXACT/OPTIMAL	10 LENGTH*	11 DRIVER TYPE
FH3 - Hardwire, 3ft wire FH6 - Hardwire, 6ft wire FH9 - Hardwire, 9ft wire FHX - Hardwire, custom length wire FC3 - DC plug, 3ft wire FC6 - DC plug, 6ft wire FC9 - DC plug, 9ft wire FCX - DC plug, custom length wire	WSE - Simple lead-in, end feed WSB - Simple lead-in, back feed WPE - Pass-through, end feed WPB - Pass-through, back feed	QE - Exact QO - Optimal Exact - length specified in section 10 with end caps without flanges. Optimal - length specified in section 10, rounded down to the closest LED cut section to minimize dark spots.	Length of the luminaire in inches. <i>*Includes end caps, excludes flanges (when applicable).</i> 	PND - Non-dimmable P010 - 0-10V dimming PPH - Phase (ELV / MLV) dimming P5i1 - 5-in-1 (Phase / 0-10V) dimming PDAL - DALI compatible driver PDMX - DMX driver PNO - No driver




ACCESSORIES (OPTIONAL)	
GYPSUM COVES	Quantity
CGAP - Apsis, 8ft	
CGLA - Latus, 8ft	
CGNI - Nidus, 8ft	
CGSU - Sulcus, 8ft	

1 Finish	2 Mounting	3 Optics	4 Lumen Package	5 CCT	6 Application	7 Power Feed	8 Input / Output	9 Exact / Optimal	10 Length, in	11 Driver Type
-	-	-	-	-	AID	-	-	-	-	-

1 PROFILE & FINISH	2 MOUNTING	3 OPTICS	4 LUMEN PACKAGE	5 CCT	6 APPLICATION
CA1100 - Anodized aluminum finish CA1101 - Anodized black finish CA110W - White (special order) CA110X - Custom color provide RAL #	MCF - Flat surface bracket MC3 - 45° Corner bracket MC8 - Swivel 180° M3M - Double face mounting tape MNO - No mounting	DCS - Clear lens DXS - Optiflex lens DOS - Opal lens DRS - Prime lens DBS - Black lens DSS - Silens DODS - 3D Opal drop square lens DNO - No lens	LDWM2465 - Dual White - 3.5 W/ft - 260 lm/ft LDWH2465 - Dual White - 5.8 W/ft - 427 lm/ft LRGBLD - RGB - 4.4 W/ft - low density LRGBMD - RGB - 5.8 W/ft - medium density LRGB30 - RGBW (3000K) 4 in 1 - 4.4 W/ft - 107 lm/ft	2400-6500K N/A RGB + 3000K	AID - Indoor dry locations


7 POWER FEED	8 INPUT / OUTPUT	9 EXACT/OPTIMAL	10 LENGTH*	11 DRIVER TYPE
FH3 - Hardwire, 3ft wire FH6 - Hardwire, 6ft wire FH9 - Hardwire, 9ft wire FHX - Hardwire, custom length wire	WSE - Simple lead-in, end feed WSB - Simple lead-in, back feed WPE - Pass-through, end feed WPB - Pass-through, back feed	QE - Exact QO - Optimal Exact - length specified in section 10 with end caps without flanges. Optimal - length specified in section 10, rounded down to the closest LED cut section to minimize dark spots.	Length of the luminaire in inches. *Includes end caps, excludes flanges (when applicable). 	PND - Non-dimmable PDMX - DMX driver PNO - No driver



ACCESSORIES (OPTIONAL)	
GYPSUM COVES	Quantity
CGAP - Apsis, 8ft	
CGLA - Latus, 8ft	
CGNI - Nidus, 8ft	
CGSU - Sulcus, 8ft	


PROFILE

1100




END CAPS

REGULAR





3D





2 - MOUNTING HARDWARE DIMENSIONS

CLIP-IN BRACKETS (stainless steel)



MCF - FLAT BRACKET



MC3 - 45° CORNER BRACKET



MC8 - SWIVEL 180° BRACKET



Scale 1:1


LED TAPE AND OPTICS CHART

@ FULL LIGHT OUTPUT

	LP100	LP200	LP300	LP450	LP750	LW2229	LW2735	LDWM	LDWH	LRGBLD	LRGBMD	LRGB30	
LED tape color type													
CCT Range	2400K 2700K 3000K 3500K 4000K					2200K to 2900K	2700K to 3500K	2400K to 6500K	2400K to 6500K	RGB	RGB	RGBW 3000K	
Power	4.8 W/m 1.5 W/ft	9.6 W/m 3.0 W/ft	14.5 W/m 4.4 W/ft	19.2 W/m 5.8 W/ft	23 W/m 7.0 W/ft	14.5 W/m 4.4 W/ft	14.5 W/m 4.4 W/ft	11.5 W/m 3.5 W/ft	19.2 W/m 5.8 W/ft	14.5 W/m 4.4 W/ft	19.2 W/m 5.8 W/ft	14.5 W/m 4.4 W/ft	
Efficacy	91 lm/W	81 lm/W	76 lm/W	84 lm/W	95 lm/W	< 44 lm/W	< 46 lm/W	74 lm/W	74 lm/W	-	-	-	
CRI	90+	90+	90+	90+	95+	90+	90+	90+	90+	-	-	80+	
R9	60+	60+	60+	60+	65+	60+*	60+*	60+*	60+*	-	-	-	
Available in IP68 option (silicone sleeve)	N	N	N	N	N	N	N	N	N	N	N	N	
LED tape increment	50 mm 1.97 in	50 mm 1.97 in	33 mm 1.30 in	25 mm 0.98 in	33 mm 1.30 in	50 mm 1.97 in	50 mm 1.97 in	50 mm 1.97 in	50 mm 1.97 in	100 mm 3.94 in	63 mm 2.48 in	100 mm 3.94 in	
Quantity of LED chips	120 LED/m 36 LED/ft	120 LED/m 36 LED/ft	180 LED/m 54 LED/ft	240 LED/m 73 LED/ft	60 LED/m 18 LED/ft	112 LED/m 34 LED/ft	60 LED/m 18 LED/ft						
LED tape width	8 mm 0.31 in	8 mm 0.31 in	8 mm 0.31 in	10 mm 0.39 in	10 mm 0.39 in	10 mm 0.39 in	10 mm 0.39 in	10 mm 0.39 in	10 mm 0.39 in	10 mm 0.39 in	10 mm 0.39 in	12 mm 0.47 in	
Spec sheet													
LENS	BEAM					*At higher CCT value		*At higher CCT value					
DBS - black	 Disappears on dark surfaces when turned off.												
DSS - silens	 No dots, suitable for direct view, and a continuous lens up to 10M (33ft).												
DOS - opal	 Diffused light. Suitable for direct view.												
DODS - 3D opal													
DRS - prime	 Best light output for direct view with higher lumen packages.												
DXS - optiflex	 Eliminates shadows, best light output for indirect view.												
DCS - clear	 The highest light output for indirect view.												
	70 lm/ft	113 lm/ft	169 lm/ft	241 lm/ft	395 lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	rgb	rgb	xx lm/ft	
	93 lm/ft	151 lm/ft	224 lm/ft	316 lm/ft	545 lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	rgb	rgb	xx lm/ft	
	98 lm/ft	155 lm/ft	233 lm/ft	339 lm/ft	567 lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	rgb	rgb	xx lm/ft	
	125 lm/ft	203 lm/ft	309 lm/ft	429 lm/ft	721 lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	rgb	rgb	xx lm/ft	
	121 lm/ft	192 lm/ft	290 lm/ft	409 lm/ft	682 lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	rgb	rgb	xx lm/ft	
	135 lm/ft	217 lm/ft	333 lm/ft	453 lm/ft	762 lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	xx lm/ft	rgb	rgb	xx lm/ft	
	158 lm/ft	252 lm/ft	379 lm/ft	525 lm/ft	870 lm/ft	<192 lm/ft	<202 lm/ft	<260 lm/ft	<427 lm/ft	rgb	rgb	107 lm/ft	

DOT-FREE

VISIBLE DOTS



Lumen output tested at 4000K. Use this table to calculate lumen output for different CCTs.

2400K - 0.89	2700K - 0.91	3000K - 0.95	3500K - 0.96	4000K - 1.00	6200K - 1.07
--------------	--------------	--------------	--------------	--------------	--------------

LUMINOSITY CALCULATION EXAMPLE:

According to the above table **LP750** lumen package with **DRS** (prime) lens for CCT **4000K** has luminosity of 682 lm/ft at CCT **3000K** lumen output is **559 lm/ft * 0.95 = 648 lm/ft**

IES FILES


for other CCTs peak candella




FC3 / FC6 / FC9 / FCX - DC CONNECTORS (static white and Warmdim LED tape only)

- FC3 - DC plug, 3ft wire
- FC9 - DC plug, 9ft wire
- FC6 - DC plug, 6ft wire
- FCX - DC plug, custom length wire

DRY APPLICATIONS



DAMP / WET APPLICATIONS



FH3 / FH6 / FH9 / FHX - HARDWARE

- FH3 - Hardware, 3ft wire
- FH9 - Hardware, 9ft wire
- FH6 - Hardware, 6ft wire
- FHX - Hardware, custom length wire

Static white / Warmdim TEW 22 AWG



Tunable White



Static white / Warmdim TR64 22 AWG



RGB



Static white / Warmdim IP68 (FT4)




RGBW



8 - INPUT / OUTPUT


1100 SIMPLE LEAD (ONE SIDE)

- WSE - End feed (no dark spots)
- WSB - Back feed (dark spots)







1100 PASS-THROUGH (TWO SIDES)


- WPE - End feed (no dark spots)
- WPB - Back feed (dark spots)




ORDERING CODE EXAMPLES



Ordering length includes the thickness of end caps and excludes flanges (where applicable).




Ordering length for a luminaire with no-flange end caps




Ordering length for a luminaire with flanged end caps

12 GYPSUM COVES - DRYWALL FORMS


APSIS




LATUS



NIDUS



SULCUS



CODE	LED TYPE	POWER SUPPLY NUMBER	POWER	CHANNELS	DIMM. PROTOCOL	DIMM. RANGE	INPUT	OUTPUT	LOCATION	DIMENSIONS	CERT.	SPECS
PND	Single Color Dual White RGB RGBW	LTPS-NODIM-100277VAC-CV-24V-96W-HW-DRBX	96W	N/A	No dimming	N/A	Hardwire	Hardwire	Dry, Damp, Wet	220 x 95 x 40mm	cULus	🔗
		LTPS-CV-120-24-1000mA-24W-PG	24W				Plug-in	DC plug	Dry	61.4 x 37.4 x 29.4mm	cETLus	🔗
		LTPS-CV-120-24-2500mA-60W-PG	60W				Plug-in	DC plug	Dry	116.5 x 51.7 x 35mm	cETLus	🔗
		LTPS-CV-120-24-4A-96W-BK-PG	96W				Plug-in	DC plug	Dry	154 x 62 x 38mm	cULus	🔗
PPH	Single Color Warm Dim	MINI-60W-120V-24V-PH-DRBX-BK	60W	N/A	ELV MLV TRIAC	0% - 100%	Enclosed	Enclosed	Dry, Damp, Wet	127 x 82 x 41.8mm	cULus	🔗
		MINI-96W-120V-24V-PH-DRBX-BK	96W				Enclosed	Enclosed	Dry, Damp, Wet	127 x 82 x 41.8mm	cULus	
P5ii	Single Color WarmDim	LTE-30W-UNV-24VAO-PH010-BK	30W	N/A	ELV MLV TRIAC 0-10V 1-10V	0.1% - 100%	Enclosed	Enclosed	Dry, Damp, Wet	170.5 x 116.5 x 42mm	cULus	🔗
		LTE-60W-UNV-24VAO-PH010-BK	60W				Enclosed	Enclosed	Dry, Damp, Wet	196.5 x 103.4 x 40mm	cULus	
		LTE-96W-UNV-24VAO-PH010-BK	96W				Enclosed	Enclosed	Dry, Damp, Wet	196.5 x 103.4 x 40mm	cULus	
		LTE-192W-UNV-24VAO-PH010-BK	192W				Enclosed	Enclosed	Dry, Damp, Wet	232 x 116 x 40mm	cULus	
		LTE-288W-UNV-24VAO-PH010-BK	288W				Enclosed	Enclosed	Dry, Damp, Wet	275 x 116 x 40mm	cULus	
PDMX	Single Color WarmDim RGB RGBW	LTX-100W-UNV-24VAO-DMX-3-BK	100W	3 Channels	DMX	0.1% - 100%	Enclosed	Enclosed	Dry, Damp, Wet	241 x 125 x 42.7mm	cULus	🔗
		LTX-100W-UNV-24VAO-DMX-5-BK	100W	5 Channels			Enclosed	Enclosed	Dry, Damp, Wet	241 x 125 x 42.7mm	cULus	

A Class 2 LED driver is designed to deliver a limited amount of electrical power to LED lighting fixtures. It refers to a set of safety standards established by the Canadian Electric Code (CEC) and the National Electrical Code (NEC), which governs the use of low-voltage power sources in buildings.

Class 2 LED drivers are important because they provide a safe and reliable power source for LED lighting systems. These drivers are designed to limit the amount of electrical current and voltage that is delivered to the LED fixtures, which helps to prevent electrical shock hazards and minimize the risk of fire or other electrical hazards.

Additionally, Class 2 LED drivers are typically more energy-efficient than other types of power supplies, which can help to reduce energy consumption and lower operating costs for LED lighting systems.