


# 4400 PROFILE

4000 Series



Cross-section dimensions:



## ONE OF THE SMALLEST ON THE MARKET

**Guaranteed to be discreet!** The 4400 profile is reduced to a minimum with its size of less than half an inch, while accepting a good range of LED engines<sup>1</sup>.

(1) Accepts LED engines up to 8mm wide.

### FEATURES

- Ultra-compact aluminum profile – 12.2mm wide by 12.2mm high (0.5 x 0.5in).
- Custom length by sections of 2 to 240 inches (6m).
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED engine.
- Designed to meet North American woodworking standards.

### LED STRIP COMPATIBILITY


Compatible with LED strips up to **8mm** wide.

### LINEAR WEIGHT

0.108 lbs/ft, 0.160 kg/m (without lens)



|                    |                      |                    |                           |                 |                         |                        |                            |                             |                         |                          |
|--------------------|----------------------|--------------------|---------------------------|-----------------|-------------------------|------------------------|----------------------------|-----------------------------|-------------------------|--------------------------|
| <b>1</b><br>Finish | <b>2</b><br>Mounting | <b>3</b><br>Optics | <b>4</b><br>Lumen Package | <b>5</b><br>CCT | <b>6</b><br>Application | <b>7</b><br>Power Feed | <b>8</b><br>Input / Output | <b>9</b><br>Exact / Optimal | <b>10</b><br>Length, in | <b>11</b><br>Driver Type |
| -                  | -                    | -                  | -                         | -               | <b>AID</b>              | -                      | -                          | -                           | -                       | -                        |

|   |   |  |   |  |  |
|---|---|--|---|--|--|
| <b>1 PROFILE &amp; FINISH</b><br>CA4400 - Anodized aluminum finish<br>CA4401 - Anodized black finish<br>CA440W - White (special order)<br>CA440X - Custom color provide RAL #   | <b>2 MOUNTING</b><br>MCF - Flat bracket<br>MND - No mounting  | <b>3 OPTICS</b><br>DCS - Clear lens<br>DOS - Opal lens<br>DSS - Silicone lens<br>DBS - Black lens<br>DNO - No lens   | <b>4 LUMEN PACKAGE</b><br>LP100 - 1.5 W/ft - >130 lm/ft<br>LP200 - 2.9 W/ft - >200 lm/ft<br>LP300 - 4.4 W/ft - >300 lm/ft<br><b>PRECISE</b><br>LE150* - 1.5 W/ft - >150 lm/ft<br>LE300 - 3.0 W/ft - >300 lm/ft<br>LE600 - 5.5 W/ft - >600 lm/ft<br><b>NEAT</b><br>LT150* - 2.0 W/ft - >150 lm/ft<br>LT300 - 3.0 W/ft - >300 lm/ft | <b>5 CCT</b><br>K24 - 2400K<br>K27 - 2700K<br>K30 - 3000K<br>K35 - 3500K<br>K40 - 4000K<br>*LE150 and LT150 are only available in K27 and K30  | <b>6 APPLICATION</b><br>AID - Indoor dry locations |
| <b>7 POWER FEED</b><br>FH3 - Hardwire, 3ft wire<br>FH6 - Hardwire, 6ft wire<br>FH9 - Hardwire, 9ft wire<br>FHX - Hardwire, custom length wire<br>FC3 - DC plug, 3ft wire<br>FC6 - DC plug, 6ft wire<br>FC9 - DC plug, 9ft wire<br>FCX - DC plug, custom length wire | <b>8 INPUT / OUTPUT</b><br>WSE - Simple lead-in, end feed<br>WSB - Simple lead-in, back feed<br>WPE - Pass-through, end feed<br>WPB - Pass-through, back feed | <b>9 EXACT/OPTIMAL</b><br>QE - Exact<br>QO - Optimal<br>Exact - length specified in section 10 with end caps without flanges.<br>Optimal - length specified in section 10, rounded down to the closest LED cut section to minimize dark spots. | <b>10 LENGTH*</b><br>Length of the luminaire in inches.<br>*Includes end caps, excludes flanges (when applicable).<br>   | <b>11 DRIVER TYPE</b><br>PND - Non-dimmable<br>P010 - 0-10V dimming<br>PPH - Phase (ELV / MLV) dimming<br>P5i1 - 5-in-1 (Phase / 0-10V) dimming<br>PDAL - DALI compatible driver<br>PDMX - DMX driver<br>PNO - No driver |  |

