

Projet: _____ **Type:** _____

T8 4ft 2pin 22-20-18-15-12-10W 120-347V 2700K-3500K-4000K-5000K-6000K-6500K

CARACTERISTICS

- -
- -
- -
- -



NOMENCLATURE

SERIE	LENGHT	WIRING	BASE TYPE	VOLTAGE	CCT	MAX POWER	LENS	CONNECTION TYPE	VER.
T8	4	2	G13	F	C	022	F	D	Z
T8	4ft	both ends wiring	2pin	120-347V	2700K-3500K-4000K-5000K-6000K-6500K	22-20-18-15-12-10W	frost	Type A+B	Z

PHOTOMETRIC SPECIFICATIONS

LUMENS	3,080
CCT	2700k/3500/4000K/5000k/6000/6500k
ANGLE	120°
C.R.I.	84
DIMMABLE	N/A
PHOTOCELL	N/A
SENSOR	N/A
LUMEN MAINTENANCE L70	50,000 hrs
LED TYPE	SMD2835
LED QTY	240
LED VOLTAGE	72V
LED MAX CURRENT	250m A
FLICKER	Flicker-Free

MECHANICAL SPECIFICATIONS

HOUSING MATERIAL	Aluminium
HOUSING FINISH	White
LENS MATERIAL	Polycarbonate
LENS FINISH	Frost
WEIGHT	0.38 KG
OPERATING TEMP.	-40°C ~ 45°C
APPLICATION	Indoor

ELECTRICAL SPECIFICATIONS


REAL POWER	22 W
VOLTAGE	120-347V
EFFICIENCY	140 lm/w
POWER FACTOR	91 %
T.H.D	23.9 %
FREQUENCY	50/60Hz

CERTIFICATIONS

REGULATORY LISTING	cETL
EFFICIENCY LISTING	DLC Standard
DLC ID	S-FZIVR0
FCC	No
BARCODE	882110007441
ENVIRONMENTAL	IP40
IK PROTECTION	
SURGE PROTECTION WITH GROUNDING	2KV
SURGE PROTECTION WITHOUT GROUNDING	1.2KV

INSTALLATION	Retro-Fit
CABLE LENGTH	N/A

DIMENSIONS



PACKAGING

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
122.00 cm X 3.00 cm X 3.00 cm 48 " X 1 1/8 " X 1 1/8 "	N/A	N/A	0.40 kg 0.88 lbs	28 

PRODUCTS IMAGES

No Product images

SPECLITE.CA | INFO@SPECLITE.CA | TEL: 1-855-533-8818
HEADQUARTER: 600-1111 BOUL. DR.-FREDERICK-PHILIPS MONTRÉAL, QC H4M 2X6
WAREHOUSE: 1710 AUTOROUTE TRANSCANADIENNE, DORVAL, QC, H9P 2X7