


Under Cabinet Puck Lights

UC-30K-R-WH-V2

Date:	Project:	Comments:
Prepared for:	Type:	



Colour
3000K



Performance Specifications

Power	2.2W
Input Voltage	12V
Input Current	0.18A
Color Temperature	3000K
Lumens	150lm
Efficacy	~68lm/W
CRI (Color Rendering Index)	>80
Lifetime	50,000 hours
Dimming	Compatible with TRIAC dimmers and drivers.
Beam Angle	110°
Environment Rating	Suitable for dry locations
Operating Temperature	-20°C to 40°C

Physical Specifications

Dimensions	Ø75mm x 7mm
Weight	55g (1.90 oz)
Body Material	Nylon
Trim Material	Steel
Lens Material	Acrylic
Cord Length	40"
Wire Size	24 AWG

Ordering Specifications

Years of Warranty	3 years
Certification and Compliances	cETLus


Ordering Information

Stock item. Orders placed by 3pm ship out the same day.

Power	Colour Temperature	Product colour	Model Number	Ordering Code
2.2W	3000K	White	QS-107T-2.2W	UC-30K-R-WH-V2




Dimensions




Note

It is recommended to use only one 6-way hub per compatible driver. Cascading the Hub is not recommended.
 For configurations with more than 6 puck lights, please contact Arani support for assistance.
 The extension cable should only be used between the hub and the 12V slim puck light. Not more than one extension cord per puck light.
 The 6-way hub includes a 2-pin male connector. If this connector is not needed for the installation, it can be cut off and the wires stripped to connect directly to a 12VDC power supply.




Photometrics

Polar Candela Distribution



Illuminance at Distance



Zonal Lumen Summary

Zone	Lumens	% Lamp	% Luminaire
0-30	49.0	31.3%	31.3%
0-40	78.9	50.4%	50.4%
0-60	133.5	85.3%	85.3%
60-90	23.0	14.7%	14.7%
70-100	6.5	4.2%	4.2%
90-120	0.000	0%	0%
0-90	156.5	100%	100%
90-180	0.000	0%	0%
0-180	156.5	100%	100%



Additional Accessories



Black Finish Trim
UC-R-TR-BK-V2



Brushed Nickel Finish Trim
UC-R-TR-BN-V2



6-Way Hub - 40"
UC-HUB-6-V2



Extension Cable (male to female) - 40"
UC-EXT-1M-V2