

Projet:	Type:	Qté:
---------	-------	------

**Vapor Tight 56W 120-347V 5000K**

The SpecLite waterproof luminaire is the ultimate solution for applications requiring steam- and water-resistant lighting. Perfectly suited to agricultural environments and buildings where these elements are ubiquitous, this IP66 luminaire offers reliable protection and exceptional durability, while ensuring enhanced energy efficiency. Designed for easy, flexible installation thanks to its three large brackets, the Vapor Tight features a polycarbonate lens with integrated suspension cable, and the diode insert is pre-assembled for easy installation and maintenance. Compatible with a 0-10V dimmer, this luminaire can be dimmed up to 10%, giving you precise lighting control. DLC Premium certified, it maximizes subsidies, making it both a cost-effective and practical solution for modernizing your lighting systems while reducing operating and maintenance costs.



**CARACTERISTICS**

- IP66 rating along with NEMA 4X certification: Resistant to water and steam, ideal for the most demanding and corrosive agricultural environments.
- Simplified installation: Equipped with three wide bracket spaces and a polycarbonate lens with an integrated suspension cable for easy setup.
- 0-10V dimming: Allows brightness reduction down to 10% for precise lighting control based on needs.
- DLC Premium Certified: Maximize your subsidies while reducing operating and maintenance costs through optimal energy efficiency.

**NOMENCLATURE**

SERIE	DIMENSIONS	LENS	BODY COLOUR	VOLTAGE	CCT	MAX POWER	OPTIONS 1	OPTIONS 2	VER.
VT	04	F	W	F	5	056	0	D	JY
Vapor tight	4ft	frost	white	120-347V	5000K	56W	N/A	dim 0-10V	JY

**PHOTOMETRIC SPECIFICATIONS**

LUMENS	7,032
CCT	5000K
ANGLE	110°
C.R.I.	86
DIMMABLE	0-10V DC
PHOTOCELL	N/A
SENSOR	N/A
LUMEN MAINTENANCE L70	75,000 hrs
LED TYPE	SMD2835
LED QTY	224
LED VOLTAGE	40V
LED MAX CURRENT	1200mA
FLICKER	Flicker-Free

**MECHANICAL SPECIFICATIONS**

HOUSING MATERIAL	Polycarbonate
HOUSING FINISH	White
LENS MATERIAL	Polycarbonate
LENS FINISH	Frost

**ELECTRICAL SPECIFICATIONS**


REAL POWER	53.4 W
VOLTAGE	120-347V
EFFICIENCY	131.69 lm/w
POWER FACTOR	96 %
T.H.D	5.1 %
FREQUENCY	50/60Hz

**CERTIFICATIONS**

REGULATORY LISTING	cUL
EFFICIENCY LISTING	DLC Premium
DLC ID	S-ILDCEF
FCC	No
BARCODE	882110006284
ENVIRONMENTAL	NEMA4X
IK PROTECTION	IK08
SURGE PROTECTION WITH GROUNDING	2KV
SURGE PROTECTION WITHOUT GROUNDING	1.6KV

<b>WEIGHT</b>	2.50 KG
<b>OPERATING TEMP.</b>	-20°C ~ 45°C
<b>APPLICATION</b>	Indoor
<b>INSTALLATION</b>	Surface Mount
<b>CABLE LENGTH</b>	N/A

## DIMENSIONS



## PACKAGING

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
121.00 cm X 13.00 cm X 10.00 cm	124.00 cm X 30.00 cm X 28.00 cm	6	17.52 kg	108 
47 5/8" X 5 1/8" X 3 7/8"	48 7/8" X 11 3/4" X 11"		38.62 lbs	

## PRODUCTS IMAGES

