

**Projet:** \_\_\_\_\_ **Type:** \_\_\_\_\_

### Area Light Accessoires - Photocellule 347V

SpecLite's Photocell with a 3-pin twist-lock connection is an essential accessory for automatic lighting management. Designed for voltages ranging from 200V to 480V, it activates your fixtures when ambient light becomes insufficient, ensuring consistent illumination from dusk to dawn.

#### CARACTERISTICS

- Universal compatibility: Suitable for round and square poles for versatile installation.
- Wide Voltage Range: Compatible with voltages from 200V to 480V.
- 3-Prong Twist-Lock Connection: Fast and secure installation.
- Constant Lighting: Ensures reliable illumination from dusk to dawn.



#### NOMENCLATURE

SERIE	VER.
ZZ	
Accessories	

#### PHOTOMETRIC SPECIFICATIONS

LUMENS	0
CCT	
ANGLE	
C.R.I.	
DIMMABLE	
PHOTOCELL	
SENSOR	
LUMEN MAINTENANCE L70	
LED TYPE	
LED QTY	
LED VOLTAGE	
LED MAX CURRENT	
FLICKER	

#### MECHANICAL SPECIFICATIONS

HOUSING MATERIAL	
HOUSING FINISH	
LENS MATERIAL	
LENS FINISH	
WEIGHT	0.10 KG
OPERATING TEMP.	
APPLICATION	Accessory
INSTALLATION	

#### ELECTRICAL SPECIFICATIONS

REAL POWER	W
VOLTAGE	
EFFICIENCY	lm/w
POWER FACTOR	%
T.H.D	
FREQUENCY	

#### CERTIFICATIONS

REGULATORY LISTING	
EFFICIENCY LISTING	
DLC ID	
FCC	
BARCODE	882110004785
ENVIRONMENTAL	
IK PROTECTION	
SURGE PROTECTION WITH GROUNDING	
SURGE PROTECTION WITHOUT GROUNDING	

CABLE LENGTH

N/A

---

## DIMENSIONS



## PACKAGING

DIMENSION INNER CARTON	DIMENSION OUTER CARTON	QUANTITY MASTER	MASTER WEIGHT	PALLET QUANTITY
10.00 cm X 8.00 cm X 8.00 cm 3 7/8 " X 3 1/8 " X 3 1/8 "	43.00 cm X 43.00 cm X 30.00 cm 16 7/8 " X 16 7/8 " X 11 3/4 "	50	5.00 kg 11.02 lbs	0 

## PRODUCTS IMAGES

No Product images

SPECLITE.CA | INFO@SPECLITE.CA | TEL: 1-855-533-8818  
**HEADQUARTER:** 600-1111 BOUL. DR.-FREDERICK-PHILIPS MONTRÉAL, QC H4M 2X6  
**WAREHOUSE:** 1710 AUTOROUTE TRANSCANADIENNE, DORVAL, QC, H9P 2X7